

S35CHPS

COLOR DAY/NIGHT BULLET CAMERA

PRECAUTIONS



• Power Requirements

The equipment should be operated only with the type of power source indicated on the marking label. This camera is designed for use with a regulated 12V DC power source.

• Impedance

This camera is to be used with a standard 75 ohm impedance monitor. On monitors with both a high and standard impedance mode, ensure the impedance mode is set to standard

• Service

Do not attempt to service the camera yourself. There are no user serviceable parts inside.

Refer servicing to a qualified service technician.

• Light Exposure

Do not aim or point the camera towards the sun or into a bright light.

SPECIFICATIONS

Image Device	1/3" super HAD SONY CCD
Signal System	60Hz
Effective Pixels	768(H) X 494(V)
Scanning System	2:1 Interlace
Sync System	Internal
Horizontal Resolution	More than 550TVL
Sensitivity	0 Lux (IR LED ON)
S / N Ratio	More than 45dB (AGC OFF)
Gamma Correction	$\gamma = 0.45$
Video Output	Composite 1Vp-p, 75(Ω) unbalanced
Electronic Shutter	1/60 ~ 1/100,000 sec Auto
Power Supply	12V DC($\pm 10\%$)
IP Rate	IP67
Operating Temperature	14° F ~ 104° F (-10°C ~ +40°C)
Storage Temperature	-22° F ~ 122° F (-30°C ~ +50°C)
Weight	6.27 oz (178g)
Dimension	37(mm) ϕ × 90(mm)
IR LED	6 Unit IR LED (10M beam length)
IR LED wavelength/half angle	850nm / ± 15 degree
Lens	f 6.0mm fixed focal board type lens.

