

Height-Strip Covert Color Camera



Features

- Color camera in covert height-strip housing
- Black anodized aluminum housing to match standard commercial doorframe
- Includes wall-mount swivel bracket
- Interfaces with standard ADT RJ-11 systems or with 12VDC power supply and BNC connector when ordered as FS100CAMB
- 3.7mm fixed iris wide-angle lens

Product Summary

The CC42HS37 and FS100CAMB feature a standard resolution color camera housed in a covert height-strip housing.

The cameras offer a wide-angle 3.7mm lens for a 92° diagonal field of view (79° horizontal, 64° vertical). The wide-angle lens allows viewing of a person's face while exiting the premises.

The video connection to the camera is a BNC connector and a power pin connector for standard 12VDC operation.

In the FS100CAMB configuration, the camera is supplied with a regulated 12VDC power supply.

In the CC42HS37 configuration, the camera is supplied with a BNC/power pin to RJ-11 adapter (Model 1512AC) for use with ADT RJ-11 systems.

NOTE: The RJ-11 camera cable, used with the CC42HS37 camera configuration must be ordered separately and is available in 60', 100', 200' and 300' lengths.

The black anodized aluminum housing may be attached to a standard commercial doorframe or may be mounted on a wall adjacent to the exit.

The swivel bracket allows adjustment of the camera's wide-angle lens to match the scene of interest.

Ordering Guide

| | |
|------------------|---|
| CC42HS37 | Color, Covert Camera, Height-Strip Housing, 3.7mm wide-angle lens |
| FS100CAMB | Color, Covert Camera, Height-Strip Housing, 3.7mm wide-angle lens, regulated 12VDC power supply |

Specifications

| | |
|------------------------------|--|
| Image Sensor | 1/3" IT CCD, 510 (H) x 492 (V) Pixels |
| Resolution | > 380 Lines |
| Lens | 3.7mm, fixed iris |
| Electronic Iris | 1/60 ~ 1/100,000 Sec. |
| Minimum Illum. | 0.5 lux, F2.0 |
| Video Output | 1.0Vp-p (75-ohms), Video BNC |
| Camera Connectors | BNC / Power (RJ-11 adapter included with CC42HS37) |
| Dimensions (WxHxD): | 2.3" x 72" x 2.7" (58mm x 1829mm x 69mm) |
| Weight | 2.4 lbs (1.1 kg) |
| Power | 12 VDC, 1.5 w (max) |
| Operating Temperature | 14°F ~ 122°F (-10°C ~ + 50°C) |

Specifications are subject to change without notice.

Optional Accessories

| Part Number | Description |
|-------------|---|
| A-A18C | 60' Camera cable |
| A-A30C | 100' Camera cable |
| A-A60C | 200' Camera cable |
| A-A90C | 300' Camera cable |
| A-MA800 | Modular cable adapter |
| A-LA800 | Line Amplifier, for camera runs over 300' |
| A-AB50C | 50' Cable, BNC to BNC |
| CONKIT4C | 4-ch A/V/A Interface with cables |
| CONKIT9C | 9-ch A/V/A Interface with cables |
| CONKIT16C | 16-ch A/V/A Interface with cables |

Dimensional Drawing

