


CATEGORY	CAMERA Quick Reference Guide													
MODEL NUMBER														
DESCRIPTION	Bullet, DN, IR LED's	Bullet, TDN, IR LED's	Bullet, TDN, IR LED's, D-WDR	Full Body, TDN, D-WDR	Full Body, TDN, Sense-Up, Envir Hsg	Interior Dome, TDN, D-WDR	Interior Dome, TDN, IR LED's, D-WDR	Vandal Dome, TDN, IR LED's, D-WDR	Vandal Dome, Extreme Weatherproof, TDN, D-WDR, Sense-Up	Compact 22X PTZ Dome	Turret Dome, Sense-Up, TDN, IR LED's, D-WDR	D/N Height Strip & Mini-Strip	License Plate Capture Camera	Tower Camera, DN
OUTDOOR IP RATING	IP67	IP67	IP67	-	IP66	-	-	IP66	IP68	IP66	IP66	-	IP66	-
IMAGE SENSOR	1/3" CCD	1/3" CCD	1/3" CCD	1/3" CCD	1/3" CCD	1/3" CCD	1/3" CCD	1/3" CCD	1/3" CCD	1/4" CCD	1/3" CCD	1/3" CCD	1/3" CCD	1/3" CCD
RESOLUTION	700 / 750 TVL	700 / 750 TVL	700 / 750 TVL	700 / 750 TVL	700 / 750 TVL	700 / 750 TVL	700 / 750 TVL	700 / 750 TVL	600 / 700 TVL	700 / 750 TVL	700 / 750 TVL	600 / 700 TVL	700 TVL (B/W Only)	600 / 700 TVL
LENS	3.6mm / 6mm	2.8-12mm VF AI	2.8 - 12mm VF AI 5 - 50mm VF AI	2.8-12mm VF AI	5-50mm VF AI	2.8-12mm VF AI	2.8-12mm VF AI	2.8-12mm VF AI	2.8-12mm VF AI	3.9-85.8mm (22x optical zoom)	2.8-12mm VF AI 5-50mm VF AI	3.7mm	5 - 50mm VF AI	3.6mm
IR LEDS	24 IR LED's (30ft outdoor range; 60ft indoor range)	30 IR LED's (60ft outdoor range; 80ft indoor range)	45 IR LED's (90ft outdoor range; 120ft indoor range)	No	No	No	30 IR LED's (100ft indoor range)	30 IR LED's (80ft outdoor range; 100ft indoor range)	IR Version: 33 IR LED's (80ft outdoor range; 100ft indoor range)	No	42 IR LED's (80ft outdoor range; 100ft indoor range)	No	10 High Power IR LED's (90ft range outdoor)	-
MIN. SCENE ILLUM. (LUX)	0.1 (Color); 0.0 (B/W)	0.1 (Color); 0.0 (B/W)	0.15 (Color); 0 (B/W, IR LED On)	0.15 (Color); 0.01 (B/W)	0.1 (Color); 0.01 (B/W)	0.15 (Color); 0.01 (B/W)	0.15 (Color); 0 (B/W)	0.15 (Color); 0 (B/W)	0.15 (Color); 0.0 (B/W, IR Version)	0.1 (Color); 0.00001 (B/W)	0.15 (Color); 0 (B/W)	0.8 (Color); 0.02 (B/W)	0 (B/W, IR LED On)	0.1 (Color); 0.04 (B/W)
WDR	No	No	Yes, Digital	Yes, Digital	Yes, Digital	Yes, Digital	Yes, Digital	Yes, Digital	Yes, Digital	Yes	Yes, Digital	No	No	-
DAY/NIGHT	Digital	TRUE	TRUE	TRUE	TRUE	TRUE	TRUE	TRUE	TRUE	TRUE	TRUE	Digital	N.A. (B/W Only)	Digital
POWER SOURCE & CONSUMPTION	12VDC Included; 375mA (IR LED On)	12VDC Included; 375mA (IR LED On)	12VDC/24VAC 420mA / 500mA (w/ Heater)	12VDC/24VAC; 240mA / 230mA	24VAC; 1.12A (Heater On)	12VDC/24VAC; 166mA / 83mA	12VDC/24VAC; 420mA / 210mA (IR LED On)	12VDC/24VAC; 420mA / 210mA (IR LED On)	12VDC/24VAC 400mA/ 170mA (Non-IR model); 850mA/650mA (IR model)	24VAC; 917mA	12VDC/24VAC 600mA / 300mA (IR LED On)	12VDC Included; 125mA	24VAC 750mA (w/ Heater)	12VDC Included; 130mA
ADDITIONAL FEATURES	Thru-Mount Wiring	Thru-Mount Wiring	Built-in Heater; TMW; Smart IR LED's; Privacy; Mirror Image	Mirror Image, Privacy, VMD, DIS, Wall Mount Incl.	Heater/Blower, Wall Mount	Mirror Image, Privacy, Digital Zoom, VMD, DIS	Mirror Image, Privacy, Digital Zoom, VMD, DIS	Mirror Image, Privacy, Digital Zoom, VMD, DIS	Built-in Heater; Mirror Image, Privacy, Digital Zoom, VMD, DIS	16X digital zoom; Heater; RS-485; Tours, Auto-Scans, Presets	16X digital zoom; VMD; DIS	Gimbal Bracket, Adjustable Height & Tilt	Built-in Heater; TMW	Adjustable Height; Base Mount Included
ACCESSORIES	-	-	A-CM150 corner mt; A-CM151 pole mt	EHWMB environmental hsg / wall mt; A-CM150 corner mt; A-CM151 pole mt; SCV55014DC 5-5mm lens	A-CM150 corner mount; A-CM151 pole mount	DB243W2(B) wall mount; PDA5W(B) pendant mount; BTCDS smoked bubble	DB243W2(B) wall mount; PDA5W(B) pendant mount; BTCDS smoked bubble	VDSMR surface mt ring; VDMWC pendant/wall mt; CV-FLUSHMT flush mt; HT202VF heater; DB243W2 wall mount; PDA5W pendant mount; BTCVS smoked bubble	TCW2-W Wall Mount; TCP-W Pendant Mount	VDMWC2 Ceiling and wall mount; DB243W2 Wall Mount; PKBD Keyboard	TCW2-W(G) wall mount, TCADP adapter plate; TCP-W(G) pendant mount	-	A-CM150 corner mt; A-CM151 pole mt	-
VIDEO CLIP	Video Link	Video Link	-	-	-	-	-	-	-	-	Video Link	-	-	Video Link
USER INSTRUCTION MANUAL	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link	HS Manual Link MS Manual Link	Manual Link	Manual Link

CATEGORY	ACCESSORIES Quick Reference Guide															
MODEL NUMBER																
DESCRIPTION	DVR Lockbox	DVR Lockbox	Heater Kit	Environmental Housing	Corner Mount	Pole Mount	Wall Mount	Wall Mount	Wall & Ceiling Mount for LV72WI camera	Wall & Ceiling Mount for A-CC722PTZ camera	Pendant Mount for Turret Camera	Wall Mount for Turret Camera	Adapter Plate for Camera	RJ-11 to BNC Adapter Cable	Keyboard Controller	
FEATURES	Provides security & protection for DVR	Provides security & protection for DVR	For use with LV72WI vandal domes	For use with A-CC600T and other full body cameras	For use with cameras and housings	For use with cameras and housings	Weather Resistant Finish	Weather Resistant Finish	Weather-Resistant Finish	Weather-Resistant Finish	Weather-Resistant Finish	Weather-Resistant Finish	Weather-Resistant Finish	For use with existing RJ-11 installations	For use with A-CC722PTZ	
	For A-ADT4HS2 DVR's	For A-ADT8H, A-ADT16H & DRC400HD DVR's	Provides protection against cold temps down to -22°F (-30°C)	IP66 rated	Light-gray polyester powder coat finish	Light-gray polyester powder coat finish	White color	Black color	White color	White color	Gray or White color	Gray or White color	White color	Converts a RJ-11 cable to work with BNC camera	Jog/Shuttle control for PTZ function	
	Made from electrolytic galvanized iron, with Removable Top Lid	Made from electrolytic galvanized iron, with Removable Top Lid	20W Power Consumption	Wall mount features TMW - Through Mount Wiring	Die cast aluminum corrosion resistant	Die cast aluminum corrosion resistant	Strong durable metal	Strong durable metal	Strong durable metal; Thru-mount wiring	Strong durable metal; Thru-mount wiring	Strong durable metal	Strong durable metal	Strong durable metal	Strong durable metal	High quality cable for excellent video signal	Controls up to 254 PTZ domes
	Rack Mount brackets; Keyed Lock on Door	Rack Mount brackets; Keyed Lock on Door	24VAC Operation Only	Includes sunshield, heater and blower for all weather conditions	Maximum load 63.5lbs	Pole diameter from 2.5" to 4.75"; Maximum load 63.5lbs	TMW - Through Mount Wiring	TMW - Through Mount Wiring	Indoor & Outdoor applications	Indoor & Outdoor applications	TMW - Through Mount Wiring	TMW - Through Mount Wiring	TMW - Through Mount Wiring	For use with A-CM150 or A-CM151	RJ-11 connector on one end; BNC and 2-pin screw terminal on other end	Program/recall presets, auto scans, patterns and tours
USER INSTRUCTION MANUAL	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link	

DVR Quick Reference Guide			
CATEGORY	DVR		
DVR MODEL NUMBER			
	A-ADT4HS2	A-ADT8H	A-ADT16H
VIDEO COMPRESSION	H.264	H.264	H.264
MAX. RECORD & PLAYBACK RATE	120-ips @ 2CIF	240-ips @ CIF	480-ips @ CIF
FILE SIZE (KB)	2 / 4 / 6 / 8 (x2 @ 2CIF, x4 @ D1)	2 / 4 / 6 / 8 (x2 @ 2CIF, x4 @ D1)	2 / 4 / 6 / 8 (x2 @ 2CIF, x4 @ D1)
VIDEO INPUTS	4 (looping)	8 (looping)	16 (looping)
HDD BAYS & SIZES	1 bay: 500GB (up to 3TB max)	2 bays: 500GB (up to 6TB max)	2 bays: 500GB, 1TB (up to 6TB max)
CONNECTIONS			
VGA	Yes	Yes	Yes
COMPOSITE	Yes	Yes	Yes
SPOT MONITOR	No	(1) Programmable / Sequenced	(1) Programmable / Sequenced
AUDIO INPUTS / OUTPUTS	1 / 1	4 / 1	4 / 1
USB	Yes (2) - v 2.0	Yes (2) - v 2.0	Yes (2) - v 2.0
ARCHIVE MEDIA	USB Flash Drive	Internal DVD-RW, USB Flash Drive	Internal DVD-RW, USB Flash Drive
ALARM IN / OUT	4 / 1	8 / 2	16 / 2
ETHERNET	RJ-45 (10/100 Base-T)	RJ-45 (10/100 Base-T)	RJ-45 (10/100 Base-T)
IR REMOTE CONTROL & MOUSE	Yes (included)	Yes (included)	Yes (included)
RECORD / SEARCH MODES			
RECORD RESOLUTION	352x240 / 704x240 / 704x480	352x240 / 704x240 / 704x480	352x240 / 704x240 / 704x480
RECORD MODE	TL, Event, Pre-event (30s), Panic	TL, Event, Pre-event (30s), Panic,	TL, Event, Pre-event (30s), Panic,
SEARCH MODE	D/T, Calendar, Event	D/T, Record Table, Calendar, Event, Motion, Museum	D/T, Record Table, Calendar, Event, Motion, Museum
OPERATION			
USER INSTRUCTION MANUAL	Manual Link	Manual Link	Manual Link
# REMOTE CONNECTIONS	2-admin, 10-watch, 2-search	2-admin, 10-watch, 2-search	2-admin, 10-watch, 2-search
# USERS	64 Groups, 256 Users	64 Groups, 256 Users	64 Groups, 256 Users
REMOTE DESKTOP	No	No	No
REMOTE ACCESSABILITY	RASPlus, Webguard	RASPlus, Webguard	RASPlus, Webguard
QUICK SETUP GUIDE	Guide Link	Guide Link	Guide Link
REMOTE HEALTHCHECK	Yes	Yes	Yes
MOBILITY SUPPORT	Android, i-Phone, iPad	Android, i-Phone, iPad	Android, i-Phone, iPad
ACCESSORIES	LB3S Lock Box	XDLBW2 Lock Box	XDLBW2 Lock Box

850 Freeport Parkway, Suite 100
Coppell, Texas 75019-4412

Matrix Support Territories

Location	Name	Number
Nat'l Sales Mgr	Paul Lange	603-303-7422
101 - Northeast	Bill O'Day	973-647-2282
102 - South Central	Jeff Swaim	336-918-6640
105 - Southwest	Mike Romeo	972-467-0421
106 - West	John Jacobsen	503-857-3207

MAIN NUMBER: 972-459-8600
 TOLL NUMBER: 877-433-6766
 TECH SUPPORT: 877-432-6766
 Updated 6/17/13